

SERIES GSA SWD Power Supply

(Three Phase)

DIN RAIL MOUNT


COMPACT SIZE

UL 508 Approved



FEATURES

Three phase input, DC low Voltage LED



SPECIFICATIONS

| | |
|----------------------|---|
| Input Voltage | 340 - 575 VAC |
| Frequency | 47 - 63 Hz |
| Output voltage | Select: 24 VDC |
| Output voltage adj. | -7 / +20% |
| Min. Efficiency | 89% |
| Temperature rating | -25°C to +71°C |
| Protection Type | Overload, Overvoltage, Over Temperature Protection, Input fuse |
| Safety Specification | EN60950 |
| Connection | Screw Terminals |

| Selection Catalog Number | GSA SWD 305 D002705 | GSA SWD 310 D002710 | GSA SWD 320 D002720 | GSA SWD 340 D002740 |
|------------------------------|--|--|---|--|
| Output Voltage | 24VDC | 24VDC | 24VDC | 24VDC |
| Output Current | 5 A | 10 A | 20 A | 40 A |
| Approval | UL 508 Listed, CE | UL 508 Listed, CE | UL 508 Listed, CE | UL 508 Listed, CE |
| Mounting | Din Rail | Din Rail | Din Rail | Din Rail |
| List Each | \$165 | \$215 | \$320 | \$575 |
| Dimensions approx. mm (Inch) | H W D 123.6 74.3 112 (4.86") (2.93") (4.41") | H W D 123.6 88 110.7 (4.86") (3.50") (4.36") | H W D 123.6 150 111.3 (4.86") (5.91") (4.38") | H W D 126 275.7 112 (4.96") (10.85") (4.41") |

