

Power Disconnects

CE UL98

UL 98, 600VAC, NFPA79, IEC 60947-1,3
10,000 Max. mechanical operations, 30A, 60A, 100Amp

30 Amp → 1200Amp
Non - Fusible
NEMA 4X Handles
3P, 4 Pole Optional

Heavy Duty Compact Modern Design

Max Amps	Item# 3 Pole	List Each	Height mm/inch with shrouds	Width mm/inch	Adjustable Depth min- max.	Short Circuit Rating at 600VAC	HP		
							240V	480V	600V
30 4X	DISC30A-*	\$150	132/5 ¹ / ₄ "	78/3.1"	4"-14"	100KA	10	20	30
30 3R	DISC30A3R-*	\$120	With Economy NEMA 3R, 12 Handle						
100 4X	DISC100A-*	\$200	132/5 ¹ / ₄ "	78/3.1"	4"- 14"	★100KA@(480V)	30	60	75
100 3R	DISC100A3R-*	\$150	With Economy NEMA 3R, 12 Handle						
200 4X	DISC200A-*	\$450	294/11.6"	180/7.1"	7"- 18"	200KA	60	125	150
400 4X	DISC400A-*	\$860	400/15.8"	232/9"	7"- 18"	200KA	125	250	350
600 4X	DISC600A-*	\$1,400	460/18.2"	280/11"	11.4"- 18"	200KA	200	400	350
800 4X	DISC800A-*	\$2,100	460/18.2"	347/13 ³ / ₄ "	11.4"- 18"	100KA	200	500	500
1,200	DISC1200A-*	\$2,500	460/18.2"	347/13 ³ / ₄ "	11.4"- 18"	100KA			

*Add Suffix to part# for handle type.
 -RG = Red / Yellow Handle. Example DISC30A-RG.
 -SI = Black handle. Example: DISC30A--SI.
 30A, 60A, 100A lugs supplied with disconnect.

★25KA @ 600VAC
 ● Padlockable
 ● Pistol Grip Style
 ● NEMA 4X
 ● All dimensions approximate

Options: 4 pole, Flange Handle, Side mount Handle Operators, check website
 For Drawings..... Min + Max Wire size 30A, 100A: AWG #12 → 2/0

Non- Fusible Part # includes Shaft, handle and Switches

1. 200mm Shaft

2. NEMA 4X 200A - 1,200A 30A, 100A Economy Handle

3. DISC 100A-*

Padlockable, by passable, double break contacts on all poles: isolates power when "off"