













Three Quality Contactor & Motor Starter Series :

SERIES	MAX AMPS	MAX HP	ELECTRICAL LIFE CYCLE	MECHANICAL LIFE CYCLE
ECX	800 A MAX	500 HP	600,000	6,000,000
EEC	700 A - 1,500 A, 1250 A Max	800 HP	1,000,000	5,000,000 , 10,000,000
AEG	1,600 A	900 HP	1,000,000	10,000,000



Features & Benefits

- 
 - 20% +10% Coil Voltage Tolerance
- 
 - 40°F + 150°F Temperature Range (EEC Type)
- 
 Compact - 45mm wide - 32 Amp Frame
75mm wide - 140 Amp (AEG)
- 
 DIN Rail Mount - Up to 140 Amp LSK Type
Metal base, ECX65 - 630, EEC40 - 780
- 
 UL 508A Supplements SB 100 kA.(EEC Type)
- 
 UL Approved suitable on a circuit capable of delivering not more than 100,000 RMS SYM.
Amps 480V Max.(EEC Type)
- 
 Side or Top Mount Auxiliaries up to 10 Max.
- 
 Ring Terminals Capable.
(EEC 12, 18, 25, 32, 115 & larger) (ECX ,18, 32)
- 
 Positive Guided (AEG LSK Series Contactors and SH05 & SH5 Relays).
- 
 RoHS: ECX, EEC, AEG up to LS55K Max.