




Type EEC AC POWER CONTACTORS 3 POLE



EEC 265

225 Amp to 500 Amp Sizes

Three Pole Contactors List Price	EEC 225- * \$ 580.00	EEC 265- * \$ 610.00	EEC 330- * \$ 786.00	EEC 400- * \$890.00	
Auxiliaries included with contactor	2 N.O.+ 1 N.C.	2 N.O.+ 1 N.C.	2 N.O.+ 1 N.C.	2 N.O.+ 1 N.C.	
AC-1 Resistive Amps	315A	350A	400A	500A	
AC-3 Motor FLA	225A	265A	330A	400A	
UL General Purpose Amps	250A	285A	360A	420A	
3 Phase Horse Power Voltage	HP	HP	HP	HP	
	200 V	55	60	75	
	230 V	65	75	100	
	460 V	135	150	200	
	600 V	175	200	250	
Dimensions					
Height	mm	197	203	206	206
Height	Inches	7.76"	7.99"	8.11"	8.11"
Width	mm	169	207	213	181
Width	Inches	6.65"	8.15"	8.39"	7.13"
Depth AC + DC Coil	mm	180	212	217	213
Depth AC + DC Coil	inches	7.09"	8.35"	8.54"	8.39"

Refer to page 12 for Coil VA data

*Coil Voltage Suffix

* - Add Suffix AC Voltage 50Hz + 60Hz	* - DC Voltage
-A 120V	-N 24VDC
-C 208V up to 220V	-O 48VDC
-E 480V	-P 125VDC
-F 600V (EEC 225 Max)	-R 220VDC
-D 380V	
-G 24V (EEC 330 Max)	
-H 277V	

Contact Factory for additional coil voltages not listed.

AUXILIARIES

2 N.O. Aux + 1N.C. **included standard** (EEC 225 + larger contactors)
Additional auxiliaries (**7 MAX**) are possible. Refer to accessory page 28.

Part # Example : EEC 225 - A = 3 Pole 2 N.O. Aux + 1 N.C. Aux , 120 VAC Coil.

UL Approved suitable on a circuit capable of delivering not more than **100,000 RMS SYM. Amps** 480 Volts Max.

**To Order "Box Lugs" See Page 28
For Sizes EEC115 - EEC400.**

- ⊕ - 40° F Min. + 158° F Max
- ⊕ 10,000,000 cycle Mechanical Life
- ⊕ 1,000,000 cycle Electrical Life
- ⊕ -15 % + 10 % Coil Voltage Range
- ⊕ - Ring terminal capable