



ADDITIONS AND SPECIAL FEATURES

MAGNETIC STARTERS AND CONTACTORS



Factory Installed Suffixes & Lists

	Additions or Special Features	Enclosure Type	Catalog Suffix Number	EEC 12	EEC 40	EEC 80	EEC 115	EEC 185	EEC 265	EEC 400	EEC 630	EEC 780	
				Thru EEC 32	Thru EEC 65	Thru EEC 95	Thru EEC 150	Thru EEC 225	Thru EEC 330	Thru EEC 500			
PILOT DEVICES IN COVER	"Start-Stop" push button.....(Twin Type)..... 1		KSS-2	\$35	\$35	\$35	\$35	\$35	\$35	\$35	\$35	\$35	
	"Start-Stop" push button.....(Twin Type)..... 4,12, 3R		KSS-3	90	90	90	90	90	90	90	90	90	
	Extra Pushbutton..... 1		-	70	70	70	70	70	70	70	70	70	
	"Up-Down-Stop" push button..... 1, 4, 12		UDS	160	160	160	160	160	160	160	160	160	
	"Forward-Reverse-Stop" push button..... 1, 4, 12		FRS	160	160	160	160	160	160	160	160	160	
	"Fast-Slow-Stop" push button..... 1, 4, 12		FSS	160	160	160	160	160	160	160	160	160	
	"Start-Stop" push button and "Hand-Off-Auto" selector switch..... Any		SS-HOA	-	180	180	180	180	180	180	180	180	180
	"Hand-Off-Auto" selector switch..... 1		HOA	35	35	35	35	35	35	35	35	35	35
	"Hand-Off-Auto" selector switch..... 4, 12, 3R		HOA	90	90	90	90	90	90	90	90	90	90
	"Forward-Off-Reverse" selector switch..... 3R, 4X, 12		FOR	90	90	90	90	90	90	90	90	90	90
"High-Off-Low" selector switch..... 3R, 4X, 12		HOL	90	90	90	90	90	90	90	90	90	90	
Pilot Light..... 1, 4, 12		PL	60	60	60	60	60	60	60	60	60	60	
"On-Off" selector switch..... 1		KSN-1	35	35	35	35	35	35	35	35	35	35	
"On-Off" selector switch..... 3R, 4, 12		KSN-3	90	90	90	90	90	90	90	90	90	90	
FULL VOLTAGE CONTROLS	Control circuit transformer Standard capacity: With fused primary and secondary 60 Hz. or 50 Hz..... 1, 4, 12		FT — V	135	135	135	280	280	340	380	380	440	
	EXTRA AUXILIARIES.....Maximum Allowable (# of Aux. Possible)..... (# of Aux. Standard).....			4	4	4	9	9	9	9	9	9	
				1N.O.	1N.O. / 1N.C	1N.O. / 1N.C	2N.O. / 1N.C	2N.O. / 1N.C	2N.O. / 1N.C	2N.O. / 1N.C	2N.O. / 1N.C	2N.O. / 1N.C	
	Add 2N.O / 2N.C. Aux..... Top Mount: Side Mount:		.22T .22S		\$17 \$22	\$17 \$22	\$17 \$22	\$17 NA	\$17 NA	\$17 NA	\$17 NA	\$17 NA	
RELAY TIMERS	Control relay (limited to one relay having maximum of 4 poles)-specify poles..... 1, 12		AR	-	204	204	204	204	320	360	360	360	
	arrangement, voltage and type required..... 4, 9		AR	-	312	312	312	312	424	472	472	472	
	Timing relay (limit of one- specify "On" or "Off" delay) 1, 12, 4		TR - 7	-	336	336	336	336	336	336	336	336	
			TR - 24	-	336	336	336	336	336	336	336	336	
	Phase Reverse Relay		FRR	-	330	330	330	330	300	300	300	300	
METERS AND METERING	Ammeter in cover (includes current transformer if necessary on Size 2 and up)-specify poles..... 1, 12		AM	-	204	204	204	204	320	360	360	360	
	Ammeter and switch..... 1, 12		AMSW	-	312	312	312	312	424	472	472	472	
	Elapsed time meter..... 1, 12		EM	-	336	336	336	336	336	336	336	336	
	Voltmeter..... 1, 12		VM	-	440	440	440	440	440	440	440	440	
	Voltmeter and switch..... 1, 12		VM SW	-	330	330	330	330	330	330	330	330	

* Applies for ALL EEC, TEC and RTEC Contactors and Starters.
Above are factory installed suffixes.
NA = Not Available.