



Type LS-K 3-Pole (Open Type) AC Contactors



New Lower List Prices Than IC - 9 Main Catalog

3 N.O Power Poles

600 Volt AC



(1 Phase) Voltage		(3 Phase) Voltage				AMPS (600)		(1) ▲ ▲ Part #	List Price	2N.O./2N.C. Auxiliary Option ●●(2) Top Mount	Special List Price	Dimensions(mm) without aux. contacts		
						Ith	UL/CSA general purpose					W	H	D
115	230	200	230	460	600	AC-1								
.75	1.5	3	3	5	7.5	25	25A	LS4K.10*	\$ 75.00	LS4K.22T-*	\$ 85.00	45	81	85/115
.75	2	3	3	7.5	10	25	25A	LS5K.10*	\$ 87.00	LS5K.22T-*	\$ 102.00	45	81	85/115
1	3	5	5	10	15	32	32A	LS7K.10*	\$ 90.00	LS7K.22T-*	\$ 105.00	45	81	85/115
1.5	3	5	7.5	15	15	45	32A	LS11K.10*	\$ 105.00	LS11K.22T-*	\$ 115.00	45	81	87/117
2	5	10	10	20	25	60	54A	LS15K.10*	\$ 145.00	LS15K.22T-*	\$ 155.00	55	87	98/134
3	5	10	10	25	25	60	55A	LS18K.11*	\$ 155.00	LS18K.22T-*	\$ 162.00	55	87	98/134
3	7.5	15	15	30	40	90	80A	LS22K.11*	\$ 160.00	LS22K.22T-*	\$ 167.00	66	117.5	116/144
5	10	20	20	40	50	110	100A	LS30K.11*	\$ 240.00	LS30K.22T-*	\$ 247.00	66	117.5	116/144
5	15	20	25	50	60	110	110A	LS37K.11*	\$ 290.00	LS37K.22T-*	\$ 297.00	66	117.5	116/144
7.5	15	25	30	60	75	140	140A	LS45K.11*	\$ 380.00	LS45K.22T-*	\$ 387.00	75	117.5	126/154
10	20	30	40	75	75	140	140A	LS55K.11*	\$ 470.00	LS55K.22T-*	\$ 477.00	75	117.5	126/154
LS4K - LS55K are 35mm DIN Rail or Screw Mount									CONTACTORS LARGER THAN LS55K HAVE SIDE MOUNT AUX.					↑ AC/DC DEPTH ↑
40	50	100	125	250	156A					LS75K.22*	\$ 800.00	135	178	165.5
50	60	125	150	250	175A					LS90K.22*	\$ 1050.00	135	178	165.5
60	75	150	150	315	175A					LS110K.22*	\$ 1,164.00	150	212	208
60	75	150	150	315	200A					LS132K.22*	\$ 1,200.00	150	212	208
100	100	250	300	450	310A					LS160K.22*	\$ 1,229.00	150	212	208
125	150	300	400	600	500A					LS220K.22*	\$ 1,720.00	160	220	228
150	200	400	500	700	600A					LS280K.22*	\$ 2,770.00	160	220	228
200	250	500	600	1000	810A					LS375K.22*	\$ 3,800.00	210	270	262
350	450	900	900	1250	1215					LS450K.22*	\$ 6,500.00	464	380	327

*** Coil Suffix - Add to Coil Suffix**

For LS4K-LS18K (3Pole)		
AC	60Hz	50Hz
-G	24	24
-A	120	120
-B	200	200
-C	220	220
-H	277	230
-E	480	380
-F	600	500
DC ADD \$30 TO LIST		
-MSW	12VDC	
-NSW	24VDC	
-OSW	48VDC	
-PSW	110VDC	
-RSW	220VDC	

For LS22K-LS55K (3Pole)		
AC	60Hz	50Hz
-G	24	24
-A	120	120
-B	200	200
-C	220	220
-H	277	230
-E	480	380
-F	600	500
DC ADD \$45 TO LIST		
-NSW	24-28VDC	
-OSW	42-48VDC	
-PSW	110-127VDC	
-RSW	220-250VDC	

For LS75K-LS375K (3Pole)	
AC/DC	50/60 Hz + DC
-GN	24-28 V
-AP	110-127V
-CR	220-250V
-EX	440-500V
No DC Adders for these sizes	
For LS450 (3&4 Pole)	
(AC ONLY)	50/60Hz
-A	110-120V
-C	220-250V
-E	360-440V

To Order:

Select from the Horse Power and voltage list the appropriate contactor size. Once the size is determined, contactor coil suffix must be designated from the chart to the left.

Example :

5 HP 230 Volt load with a 120 VAC coil.
Part # : LS7K.10- A, List \$90.00.

(1) ▲ ▲ = For NEMA Labelled Contactors
Add Suffix - NA.No Additional Charge.