



TYPE RXLSK AC STARTERS

3 Phase Full Voltage-Across the Line



All Starters Supplied with BUILT-IN HEATERS Size 3-5

NEMA RATED

AC-1 AMPS	AC-3 AMPS	Horse Power Ratings 3 Phase Motor Max UL Volts HP	OPEN	ENCLOSED					NEMA HP
				NEMA 1 General Purpose (metal)	NEMA 4X Outdoor Dust Tight (non metal)	NEMA 4 (metal)	NEMA3R Rain Tight (metal)	NEMA12 Dust Tight (metal)	
140A	95A	200V 25 HP 230V 30 HP 460V 60 HP 600V 75 HP	RXLS45K -★0-★★	RXLS45K -★1-★★	RXLS45K -★4x-★★	RXLS45K -★4-★★	RXLS45K -★3R-★★	RXLS45K -★12-★★	
		LIST	\$910	\$1,151	\$1,263	\$1,450	\$1,199	\$1,440	
140A	105A	200V 30 HP 230V 40 HP 460V 75 HP 600V 75 HP	RXLS55K -★0-★★	RXLS55K -★1-★★	RXLS55K -★4x-★★	RXLS55K -★4-★★	RXLS55K -★3R-★★	RXLS55K -★12-★★	200V 25 HP 230V 30 HP 460V 50 HP 600V 50 HP NEMA 3
		LIST	\$1,090	\$1,331	\$1,443	\$1,850	\$1,395	\$1,840	
250A	150A	200V 40 HP 230V 50 HP 460V 100 HP 600V 125 HP	RXLS75K -★0-★★	RXLS75K -★1-★★	RXLS75K -★4x-★★	RXLS75K -★4-★★	RXLS75K -★3R-★★	RXLS75K -★12-★★	
		LIST	\$1,855	\$2,100	\$2,505	\$2,675	\$2,464	\$2,665	
250A	185A	200V 50 HP 230V 60 HP 460V 125 HP 600V 150 HP	RXLS90K -★0-★★	RXLS90K -★1-★★	RXLS90K -★4x-★★	RXLS90K -★4-★★	RXLS90K -★3R-★★	RXLS90K -★12-★★	200V 40 HP 230V 50 HP 460V 100 HP 600V 100HP NEMA 4
		LIST	\$2,355	\$2,600	\$3,005	\$3,425	\$2,884	\$3,415	
315A	205A	200V 60 HP 230V 75 HP 460V 150 HP 600V 150HP	RXLS110K -★0-★★	RXLS110K -★1-★★	RXLS110K -★4x-★★	RXLS110K -★4-★★	RXLS110K -★3R-★★	RXLS110K -★12-★★	
		LIST	\$2,583	\$3,308	\$4,143	\$4,413	\$4,090	\$4,403	
315A	250A	200V 60 HP 230V 75HP 460V 150 HP 600V 150HP	RXLS132K -★0-★★	RXLS132K -★1-★★	RXLS132K -★4x-★★	RXLS132K -★4-★★	RXLS132K -★3R-★★	RXLS132K -★12-★★	
		LIST	\$2,860	\$3,585	\$4,420	\$4,680	\$4,162	\$4,670	
450A	309A	200V 100 HP 230V 100HP 460V 250 HP 600V 300HP	RXLS160K -★0-★★	RXLS160K -★1-★★	RXLS160K -★4x-★★	RXLS160K -★4-★★	RXLS160K -★3R-★★	RXLS160K -★12-★★	200V 75 HP 230V 100 HP 460V 200 HP 600V 200 HP NEMA 5
		LIST	\$2,948	\$3,673	\$4,508	\$4,830	\$4,250	\$4,820	
600A	420A	200V 125HP 230V 150HP 460V 300HP 600V 400HP	RXLS220K -★0-★★	RXLS220K -★1-★★	RXLS220K -★4x-★★	RXLS220K -★4-★★	RXLS220K -★3R-★★	RXLS220K -★12-★★	
		LIST	\$4,050	\$5,350	\$5,750	\$6,673	\$6,599	\$6,663	
700A	550A	200V 150HP 230V 200HP 460V 400HP 600V 500HP	RXLS280K -★0-★★	RXLS280K -★1-★★	RXLS280K -★4x-★★	RXLS280K -★4-★★	RXLS280K -★3R-★★	RXLS280K -★12-★★	
		LIST	\$6,150	\$7,450	\$7,850	\$8,673	\$8,488	\$8,663	

* Coil Suffix

For LS4K-LS18K (3 pole)		
AC	60Hz	50HZ
-G	24	24
-A	120	120
-B	200	200
-C	220	220
-H	277	230
-E	480	380
-F	600	500
DC add \$60 to list		
-MSW	12 VDC	
-NSW	24VDC	
-OSW	48 VDC	
-PSW	110 VDC	
-RSW	220 VDC	

For LS22K-LS55K (3 pole)		
AC	60Hz	50HZ
-G	24	24
-A	120	120
-B	200	200
-C	220	220
-H	277	230
-E	480	380
-F	600	500
DC add \$90 to list		
-NSW	24-28 VDC	
-OSW	42-48 VDC	
-PSW	110-127 VDC	
-RSW	220-250 VDC	

For LS75K-LS375K (3 Pole)	
AC/DC	50/60 Hz + DC
-N	24-28V
-AP	110-127V
-CR	220-250V
-EX	440-500V

No Addition for DC above.

Part # Example: XLS45K:
 XLS45K= Size LS45K Contactor
 A= 120 VAC Coil
 1= NEMA 1 Enclosure
 Q= 30-43 Amps

Complete Part Number:
 XLS45K-AI-Q

** Overload Relay Suffix			
O.L. Relay Setting Range		O.L. Relay Setting Range	
Suffix	(Amps)	Suffix	(Amps)
-B	0.16-0.26	-ON	21-26
-C	0.25-0.41	-P	25-32
-D	0.4-0.65	-Q	30-43
-E	0.65-1.1	-QN	42-55
-F	1.1.5	-RN	54-65
-G	1.3-1.9	-SN	64-82
-H	1.8-2.7	-TM	78-97
-I	2.5-4	-TN	90-110
-K	4-6.3	-TT	110-140
-L	5.5-8.5	-U	140-190
-M	8-12	-V	175-280
-N	10-16	-W	200-310
-O	14.5-18	-WT	250-400
-OM	17.5-22	-X	315-500

Discount Schedule ST

Modification & Accessories
 See Page 60, 61

For Technical Details on Reversing Starters See Page 50,53,68,69